

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

| | | |
|---|-----------|--|
| (51) International Patent Classification ⁶ : C09K 3/10, B65D 83/14 | A1 | (11) International Publication Number: WO 97/01611 (43) International Publication Date: 16 January 1997 (16.01.97) |
| (21) International Application Number: PCT/GB96/01551 (22) International Filing Date: 27 June 1996 (27.06.96) (30) Priority Data: 9513084.5 27 June 1995 (27.06.95) GB (71) Applicant (for all designated States except US): BESPAC PLC [GB/GB]; Bergen Way, North Lynn Industrial Estate, King's Lynn, Norfolk PE30 2JJ (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): THOMAS, Jonathan [GB/GB]; 18 Jermyn Road, Gaywood, King's Lynn, Norfolk PE30 4AE (GB). (74) Agent: BOULT WADE TENNANT; 27 Fumival Street, London EC4A 1PQ (GB). | | (81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> |
| (54) Title: DISPENSING APPARATUS (57) Abstract Dispensing apparatus for dispensing pressurised fluid comprising a valve body defining a chamber and a valve member extending movably through the chamber and through at least one annular seal co-operating with the valve member and the body to regulate the discharge of fluid. The seal is formed from a material comprising <u>A</u> a copolymer of ethylene and propylene or <u>B</u> a terpolymer of ethylene, propylene and a diene, or <u>C</u> a material selected from isobutylene isoprene, polychloroprene or fluorinated rubber. The seal may contain a mineral filler. | | |

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

| | | | | | |
|----|--------------------------|----|--|----|--------------------------|
| AM | Armenia | GB | United Kingdom | MW | Malawi |
| AT | Austria | GE | Georgia | MX | Mexico |
| AU | Australia | GN | Guinea | NE | Niger |
| BB | Barbados | GR | Greece | NL | Netherlands |
| BE | Belgium | HU | Hungary | NO | Norway |
| BF | Burkina Faso | IE | Ireland | NZ | New Zealand |
| BG | Bulgaria | IT | Italy | PL | Poland |
| BJ | Benin | JP | Japan | PT | Portugal |
| BR | Brazil | KE | Kenya | RO | Romania |
| BY | Belarus | KG | Kyrgyzstan | RU | Russian Federation |
| CA | Canada | KP | Democratic People's Republic of Korea | SD | Sudan |
| CF | Central African Republic | KR | Republic of Korea | SE | Sweden |
| CG | Congo | KZ | Kazakhstan | SG | Singapore |
| CH | Switzerland | LI | Liechtenstein | SI | Slovenia |
| CI | Côte d'Ivoire | LK | Sri Lanka | SK | Slovakia |
| CM | Cameroon | LR | Liberia | SN | Senegal |
| CN | China | LT | Lithuania | SZ | Swaziland |
| CS | Czechoslovakia | LU | Luxembourg | TD | Chad |
| CZ | Czech Republic | LV | Latvia | TG | Togo |
| DE | Germany | MC | Monaco | TJ | Tajikistan |
| DK | Denmark | MD | Republic of Moldova | TT | Trinidad and Tobago |
| EE | Estonia | MG | Madagascar | UA | Ukraine |
| ES | Spain | ML | Mali | UG | Uganda |
| FI | Finland | MN | Mongolia | US | United States of America |
| FR | France | MR | Mauritania | UZ | Uzbekistan |
| GA | Gabon | | | VN | Viet Nam |

- 1 -

"DISPENSING APPARATUS"

5 This invention relates to a dispensing apparatus for dispensing pressurised fluid in the form of an aerosol and in particular but not exclusively for dispensing medicine or products in solution or suspension in an alcohol base.

10 It is known from GB-1201918 for example to provide dispensing apparatus in which pressurised fluid from a pressurised dispensing container is released by a valve in a controlled manner, the valve including elastomeric seals which are annular and which co-operate with a sliding valve stem to open and close fluid ports.

15 Products to be dispensed are commonly provided in solution or suspension in an alcohol base, this being particularly common in the dispensing of medicinal compounds for inhalation therapy.

20 Typical apparatus includes a CFC volatile propellant having a liquid phase in which the product together with the alcohol carrier is readily soluble within the container and a typical material for the valve seal is a synthetic rubber such as nitrile rubber.

25 Recent trends in the production of aerosol dispensers have moved away from CFC propellants because of their environmental hazards and HFC propellants are now being introduced. A problem with such propellants is that alcohol is less soluble in the liquid phase of such propellants and tends to
30 separate within the container thereby exposing the valve seals to a much greater concentration of alcohol than was formerly the case. Seal materials such as nitrile rubber allow alcohol vapour to escape by
35 permeation over extended storage periods so that the

- 2 -

remaining quantity of alcohol is significantly depleted.

5 It is an object of the present invention to provide dispensing apparatus which will allow the use of HFC propellants with alcohol based products without the above disadvantage.

10 According to the present invention there is disclosed dispensing apparatus for dispensing pressurised fluid comprising a valve body defining a chamber, a valve member extending movably through the chamber and through at least one annular seal co-operating with the valve member and the body to regulate the discharge of fluid, wherein the or at least one of the seals is formed from a material
15 comprising (a) a copolymer of ethylene and propylene or
(b) a terpolymer of ethylene, propylene and a diene, or (c) a material selected from isobutylene isoprene, polychloroprene or a fluorinated rubber.

20 It has been found that the extent to which alcohol evaporates from such apparatus using such seal materials is significantly decreased so that typically a required shelf life of three years can be readily achieved.

25 Preferably the material comprises a peroxide curing agent.

A peroxide curing agent such as dicumyl peroxide is preferable to other curing agents such as sulphur since its use minimises the formation of extractives
30 (e.g. 2-mercaptobenzothiazole, N-nitrosamines, mercaptobenzothiazole disulphide) resulting from contact between the material and alcohol in use.

Preferably the seal material comprises a mineral filler.

35 Mineral fillers are preferable to carbon black in

- 3 -

order to minimise the formation of polynuclear aromatic hydrocarbon compounds.

Advantageously the mineral filler is selected from the group comprising magnesium silicate, aluminium silicate, silica titanium oxide, zinc oxide, calcium carbonate, magnesium carbonate, magnesium aluminium silicate, aluminium hydroxide, talc, kaolin and clay. Preferably the filler is magnesium silicate or kaolin.

Preferably the apparatus comprises a pressurised dispensing container operatively connected to the valve body and containing the fluid to be dispensed and a hydrofluorocarbon propellant comprising propellant type 134a or 227.

(The designation of propellant types referred to in the present application is as specified in British Standard BS4580:1970 "Specification for number designations of organic refrigerants". Accordingly, propellant 134a is:

1,1,1,2-Tetrafluoroethane $\text{CH}_2\text{F}-\text{CF}_3$
and propellant 227 is:
1,1,1,2,3,3,3 Heptafluoropropane $\text{CF}_3-\text{CHF}-\text{CF}_3$).

Typically the fluid to be dispensed comprises a liquid or particulate product as a solution or suspension in a carrier liquid comprising an alcohol such as ethanol.

A preferred embodiment of the present invention will now be described by way of example.

In a pressurised dispensing container of the type disclosed in GB-1201918, a valve body is provided with two annular valve seals through which a valve member is axially slidable, the seals being disposed at inlet and outlet apertures of a valve chamber so that the valve functions as a metering valve.

In accordance with the present invention the

- 4 -

seals are formed from a material comprising a copolymer of ethylene and propylene (EPM) cured using dicumyl peroxide as curing agent and containing magnesium silicate as a filler.

5 Satisfactory results have been obtained using such seals where the fluid to be dispensed comprises up to 50% by weight of ethanol and the propellant is of type 134a.

10 It has also been found that seals formed from a terpolymer of ethylene, propylene and a diene (EPDM) show substantially improved leakage characteristics using magnesium silicate or kaolin as a filler. This is illustrated with reference to Figure 1 and 2 which are graphs showing weight loss of test devices under
15 two different temperature testing regimes AT 30°C and 40°C respectively.

 In each case, the columns show weight loss from a dispensing device of the type described above in which the containers were filled with propellant 134A
20 ethanol and an active compound. The first column in each case shows the weight loss using a current EPDM material sold under the commercial name RB701C and which contains Ultrasil filler. The remaining columns show weight loss of corresponding devices using
25 magnesium silicate or kaolin as fillers. The respective fillers are indicated on the columns of the graphs.

 In each case, the left hand axis shows annualised weight loss calculated from tests with groups of ten
30 dispensing devices as time interval of 3 to 6 months after manufacturing and under different temperature regimes as indicated in the headings to the graphs.

 These tests show that using magnesium silicate or kaolin as a filler leads to a reduced weight loss
35 under the test regimes thus indicating lower leakage

- 5 -

from the devices. Similar results are obtained at ambient temperatures.

5

10

15

20

25

30

35

CLAIMS:

1. Dispensing apparatus for dispensing
pressurised fluid comprising a valve body defining a
5 chamber, a valve member extending movably through the
chamber and through at least one annular seal
co-operating with the valve member and the body to
regulate the discharge of fluid, wherein the or at
least one of the seals is formed from a material
10 comprising (a) a copolymer of ethylene and propylene
or (b) a terpolymer of ethylene, propylene and a
diene, or (c) a material selected from isobutylene
isoprene, polychloroprene or a fluorinated rubber.
- 15 2. Apparatus as claimed in claim 1 wherein the
material comprises a peroxide curing agent.
3. Apparatus as claimed in claim 2 wherein the
curing agent is dicumyl peroxide.
20
4. Apparatus as claimed in any preceding claim
wherein the seal material comprises a mineral filler.
- 25 5. Apparatus as claimed in claim 4 wherein the
mineral filler is selected from the group comprising
magnesium silicate, aluminium silicate, silica,
titanium oxide, zinc oxide, calcium carbonate,
magnesium carbonate, magnesium aluminium silicate,
aluminium hydroxide, talc, kaolin and clay.
30
6. Apparatus as claimed in claim 4 in which the
or at least one of the seals is formed from a material
comprising a co-polymer of ethylene and propylene and
the mineral filler is magnesium silicate.
35

- 7 -

7. Apparatus as claimed in any one of claims 1 to 5 in which the or least one of the seals is formed from a terpolymer of ethylene, propylene and a diene and mineral filler is selected from magnesium silicate or kaolin.

8. Apparatus as claimed in any preceding claim comprising a pressurised dispensing container operatively connected to the valve body and containing the fluid to be dispensed and a hydrofluorocarbon propellant comprising propellant type 134a or 227.


9. Apparatus as claimed in claim 6 wherein the fluid to be dispensed comprises a liquid or particulate product as a solution or suspension in a carrier liquid comprising alcohol.

10. Apparatus as claimed in claim 7 wherein the alcohol comprises ethanol.

1/2

FIG. 1

Weight loss Study with modified EPDMs
 30°C/70% RH, invertedly stored, n= 10 cans, time intervall 3-6 month after manufacturing




2/2

FIG. 2.

Weight loss study with modified EPDMs

40°C/75% RH, invertedly stored, n= 10 cans, time interval 3-6 month after manufacturing



INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 96/01551

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 C09K3/10 B65D83/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 C09K B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|------------|--|-----------------------|
| X | WO,A,95 02651 (MINNESOTA MINING AND MANUFACTURING COMPANY) 26 January 1995 see page 5, line 26 - page 6, line 3 see page 8, line 27 - page 10, line 9 see claim 1 | 1,8 |
| X | FR,A,2 549 568 (AEROSOL INVENTIONS AND DEVELOPMENT) 25 January 1985 see claims 1,2 | 1 |
| A | US,A,4 575 522 (BREACH ET AL.) 11 March 1986 see column 2, line 51 - column 3, line 4 see claims 1,16 | 1,2 |
| | --- | |
| | --- | |
| | --- | |
| | ---/--- | |

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

6 September 1996

Date of mailing of the international search report

27.09.96

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Puetz, C

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 96/01551

| C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT | | |
|--|--|-----------------------|
| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
| A | US,A,5 290 539 (MARECKI) 1 March 1994 see column 1, line 36 - line 54 see column 2, line 31 - line 68 see claims 1,18-20 --- | 1,8 |
| A | WO,A,95 03984 (MINNESOTA MINING AND MANUFACTURING COMPANY) 9 February 1995 --- | 1,6 |
| A | GB,A,2 148 912 (AEROSOL INVENTIONS AND DEVELOPMENT) 5 June 1985 see claims 1-3 --- | 1,4,5 |
| A | WO,A,94 25373 (MINNESOTA MINING AND MANUFACTURING COMPANY) 10 November 1994 see the whole document --- | 1,4,5,8 |
| A | WO,A,93 22221 (MINNESOTA MINING AND MANUFACTURING COPANY) 11 November 1993 see the whole document --- | 1,8 |
| A | FR,A,2 705 951 (L'OREAL) 9 December 1994 see page 2, line 7 - line 14 see page 2, line 21 - line 27 see page 5, line 32 - page 6, line 6 see claims 1,6,9 ----- | 1 |

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 96/01551

| Patent document cited in search report | Publication date | Patent family member(s) | Publication date |
|---|---------------------|--|--|
| WO-A-9502651 | 26-01-95 | AU-B- 7395694 EP-A- 0708805 | 13-02-95 01-05-96 |
| FR-A-2549568 | 25-01-85 | NONE | |
| US-A-4575522 | 11-03-86 | US-A- 4684687 | 04-08-87 |
| US-A-5290539 | 01-03-94 | AU-B- 4576096 AU-B- 5075596 AU-B- 665938 AU-B- 9167991 CA-A- 2098727 DE-D- 69114725 DE-T- 69114725 EP-A- 0562032 EP-A- 0673857 JP-T- 6504307 NZ-A- 241170 WO-A- 9211190 | 09-05-96 27-06-96 25-01-96 22-07-92 22-06-92 21-12-95 28-03-96 29-09-93 27-09-95 19-05-94 27-04-94 09-07-92 |
| WO-A-9503984 | 09-02-95 | US-A- 5474758 AU-B- 7209894 CA-A- 2167696 EP-A- 0710209 | 12-12-95 28-02-95 09-02-95 08-05-96 |
| GB-A-2148912 | 05-06-85 | NONE | |
| WO-A-9425373 | 10-11-94 | AU-B- 6665994 CA-A- 2161632 EP-A- 0697002 | 21-11-94 10-11-94 21-02-96 |
| WO-A-9322221 | 11-11-93 | AU-B- 4238393 EP-A- 0639148 | 29-11-93 22-02-95 |
| FR-A-2705951 | 09-12-94 | EP-A- 0652842 WO-A- 9429190 | 17-05-95 22-12-94 |